

Spectralink Versity

Industry Savvy.
Purpose-Built.
User Preferred.



Available in the
Cisco
Marketplace

Redefining Mobile Communications

- Versity offers best-in-class Wi-Fi and LTE coverage to keep your employees connected.
- Proprietary VQO technology ensures crystal clear communication and superior voice quality while roaming, with echo and noise cancellation.

Purpose-Built for a 24x7 Enterprise

- Versity delivers uninterrupted communication around the clock, giving workers constant access to the data and teams they need.
- True hot swappable batteries enable zero downtime, even while the phone is in use.

Open Platform for Innovation

- Open, Android platform helps you keep pace with new mobile technologies.
- Integration with the industry's largest ecosystem of application partners supports your business workflows.

User-Friendly Design

- Only 12.2 mm thick, Versity delivers the sleekest, lightest enterprise smartphone on the market.
- Durable, IP68 rated. Resistant to dust, drops and liquids, it helps achieve optimal performance in the harshest environments.



Spectralink Versity measures up to your toughest enterprise requirements without compromising style, flexibility or performance.



Specifications

MODELS

STANDARD:

- 9540 Smartphone
- 9553 w/ barcode scanner

LTE OPTION:

- 9640 Smartphone with LTE
- 9653 w/ barcode scanner

OPERATING SYSTEM

- Android™ OS 8.1 and later

WEIGHT/DIMENSIONS

- Weight: 204g, 214g (scanner)
- Width: 153 x 76 x 12mm

BATTERY/PROCESSOR

- True hot-swappable batteries (3000 mAh)
- 2.1/1.8 GhZ Octa core 64-bit processor

PERFORMANCE

- Front and Rear Camera 8 and 13MP with flash
- 64GB Storage
- CPU Memory 4GB
- HD voice and integrated full-duplex speakerphone

BARCODE SCANNER

- Industrial-strength

RADIO FREQUENCIES

- 2.4 and 5 GHz
- (802.11 a/b/g/n/d/h/i/k/r/u/ac)

BLUETOOTH ENABLED

- Bluetooth 5.0

DUST/LIQUID RESISTANCE

- IP68 – protects against dust ingress
- Waterproof – survives water submersion > 1 meter for 30+ minutes

DISPLAY AND TOUCHSCREEN

- 5.2" 1080x1920 display

DURABILITY

- Mil Spec 810 drop test – survives 78 1.8 meter drops onto steel plate
- Damage resistant Gorilla™ glass
- Recessed display for screen protection

ENVIRONMENTAL

- Operational temperature: 32 - 104° F (0 - 40° C)
- Storage temperature: -22 -140° F (-30 - 60° C)

INTERFACES

- USB type C
- 3.5 mm 4-conductor stereo headset connector
- Bluetooth and Bluetooth LE 5.0
- Near Field Communication (NFC)
- Real-Time System Location (RTLS)
- 4G LTE option

QUALITY OF SERVICE (QOS)

- Spectralink Voice Quality Optimization (VQO)
- Wi-Fi Multimedia (WMM)
- WMM-Power Save
- DSCP tagging

SECURITY

- Fingerprint sign-on capable
- Pin authorization for shared devices
- WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP- MSCHAPv2) with Opportunistic Key Caching (OKC) and Cisco Client Key Management (CCKM)
- HTTPS secure configuration and monitoring

NETWORKING STANDARDS

- Manual or Dynamic Host Configuration Protocol (DHCP)
- Domain Name Service (DNS)
- Simple Network Time Protocol (SNTP)
- Lightweight Directory Access Protocol (LDAP)
- XML and XHTML

ACCESSORIES

- USB type C wall charger
- Modular multi-charger system (Desktop charger, battery charger, multi-charger base)
- Cases (Leather case, silicone case)
- Belt clip
- Stylus

ENTERPRISE-GRADE DEVICE MANAGEMENT

- Spectralink Application Manager (SAM)
- Integration with major EMMs (i.e. SOTI, Airwatch)

PARTNER APPLICATIONS

- See spectralink.com/aims-partners for list of application partners

ADDITIONAL FEATURES

- Enterprise-grade security options
- Push-to-Talk (PTT)
- SAFE features (Alarm button, motion detection)
- Over-the-air configuration settings and updates
- PBX integration (SIP direct, gateway)
- Multilingual user interface

Learn More

Learn what Spectralink wireless handsets can do for your organization.

Visit us at spectralink.com or contact your Spectralink representative.

Android is a trademark of Google LLC. Oreo is a trademark of Mondelez International, Inc. group.



spectralink.com

info@spectralink.com

+1 800-775-5330 North America

+45 7560 2850 EMEA