

Spectralink 7532

Stylish and Feature-rich Handset for Administrative Personnel



The Spectralink 7532 wireless DECT handset is elegant yet robust with a long list of features specially designed to increase user, as well as business productivity. The large color display and the intuitive menu structure makes the handset a valuable and preferred choice for mobile workers in administrative environments across the range of vertical markets.

Business Benefits

Ease of use is key for any handset. Without it, the handset fails to be a valuable tool for the employee on the move. The Spectralink 7532 wireless DECT handset leverages an intuitive design – making it easy to use for any user.

With the Spectralink 7532 handset, employees benefit from increased productivity and optimized daily workflow with easier and faster access to the information they need to perform their day to day tasks.

The Spectralink 7532 handset is certified and tested with Cisco CUCM and HCS platforms.

Benefits

- Certified and tested with market leading Call Control and UC platforms
- Specialized features for administrative working environments
- Large color screen and intuitive menu structure
- Combines elegance and durability
- Increases productivity and optimizes workflow

Features

SPECTRALINK 7532

- TFT color display:
 - 65,000 colors
 - Eight lines of text/icons
 - 128 x 160 pixels
- Full Slot DECT radio
- Date and time in display*
- Four-way navigation key
- Auto key lock
- 12 different ringtones and adjustable ring volume
- Adjustable alerting volume (low battery/low coverage/incoming message)

- Alerting on silent mode (display flash, vibrator, or short ring)
- CLIP
- Telephone book with 350 entries
- Call list of incoming/missed/received
- Call list size: 402

* *System dependent feature. See Feature Reference Guide on support pages at support.spectralink.com for details.*

Specifications

APPROVALS

- Council Directives 2014/53/EU (Radio Emissions Directive), 2011/65/EU (RoHS II), 2014/35/EU (Low Voltage Directive)
- EN 300 328 v2.1.1 (2016-11)
- EN 301 489-1 v2.1.1 (2017-02)
- EN 301 489-6 v2.1.1 (2016-11)
- EN 301 406 v2.2.2 (2016-09)
- EN 60950-1:2006 + A 11:2009 + A1:2010 + A12:2011 + A2:2013
- EN 50360:2001 + AC:2006 + A1 :2012
- EN 50566: 2013 + AC:2014
- EN 50332-2: 2013
- EN 60529: 1991 + A1:2000 + AC:1993 + A2:2013

Note: For latest approvals and regulatory compliance, please check our website.

SPEECH / STANDBY TIME

- Speech/standby time: up to 14/114 hours

SIZE AND WEIGHT

- Size: 5.7 x 1.9 x 0.7 in. (146 x 48 x 19 mm)
- Weight: 3.9 oz incl. battery (110 g incl. battery)

BATTERY

- Battery: Li-ion battery
- Easy battery change
- Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

OPERATING TEMPERATURE

- Incl. charging: 32°F - 104°F (0 - 40°C)

TESTS

- Drop test: IEC 60068-2-32

7532 / CISCO SKUS

- SP-SLNK-7532-EU (EMEA)
- SP-SLNK-7532-AU (Australia)
- SP-SLNK-7532-NZ (New Zealand)
- SP-SLNK-7532-NA (North America/Canada)

Learn More

Learn what Spectralink wireless telephones, in partnership with Cisco®, can do for your organisation. Visit us at spectralinkplus.com or call your Spectralink representative.